

ARCHITECTURAL

**GRATES + DRAINS** 



## 65G100 Linear Drain

Developed for high capacity drainage needs, providing flexibility in landscape and pool design.

100mm Drainpipe with 65G UPVC Channel.

A 65mm wide UPVC channel is connected via downpipes at 200mm intervals to sockets in a 100mm drain below.

This allows the channel to be installed level while the drainpipe is given sufficient fall to be self-cleaning.

The Special Assembly is then completed with a stainless steel grate from the AR, TR or PS series.

Please be aware that depending on the installation environment, for a pool installation or close to a surf beach, you may need to have your stainless steel grates electropolished.

This unique drainage system was recognised for its innovation by a DesignMark at the Australian International Design Awards.

Please note stainless steel grates to complement this system are separete items

## **SPECIFICATIONS + DIMENSIONS**

Channel Width **Channel Depth** Length(s) **Outlet Size** 

74mm 42mm 3000mm N/A

## **PRODUCT APPLICATIONS**

**Balcony Drainage Commercial Drainage** Courtyard / Patio Drainage **Driveway Drainage** Pool and Spa Area Drainage Paved Area Drainage


Special Needs Drainage Suspended Slab Drainage

Copyright © Stormtech Pty Ltd. Patent 733361. Drawings not to scale, please use dimensions shown. Downloaded 07/05/2024 (please check for updates)



Visit **stormtech.com.au** for tools + inspiration.

Phone 1300 653 403 Email info@stormtech.com.au



Code 65G100 Range Special Assembly Category Modular Kits Channel Material uPVC

Grates longer than 1500mm supplied in sections. Tile Inserts longer than 1200mm supplied in sections. Channels over 3000mm supplied in sections with joiner. +/-2mm tolerance on dimensions.