

Code 65G90

Range Special Assembly

Category Modular Kits

Channel Material uPVC

90mm



65G90

Linear Drain

Developed for high capacity drainage needs, providing flexibility in landscape and pool design.

90mm Drainpipe with 65G UPVC Channel.

A 65mm wide UPVC channel is connected via downpipes at 200mm intervals to sockets in a 90mm drain below.

This allows the channel to be installed level while the drainpipe is given sufficient fall to be self-cleaning.

The Special Assembly is then completed with a stainless steel grate from the AR, TR or PS series.

Please be aware that depending on the installation environment, for a pool installation or close to a surf beach, you may need to have your stainless steel grates electropolished.

This unique drainage system was recognised for its innovation by a DesignMark at the Australian International Design Awards.

Please note stainless steel grates to complement this system are separete items

Adjustable DN40

74.2mm

Grates longer than 1500mm supplied in sections. Tile Inserts longer than 1200mm supplied in sections. Channels over 3000mm supplied in sections with joiner. +/-2mm tolerance on dimensions.

SPECIFICATIONS + DIMENSIONS

Channel Width 74mm
Channel Depth 42mm
Length(s) 3000mm
Outlet Size N/A

PRODUCT APPLICATIONS

Aged / Health Care Drainage Balcony Drainage Commercial Drainage Courtyard / Patio Drainage Driveway Drainage Pool and Spa Area Drainage Paved Area Drainage Special Needs Drainage Suspended Slab Drainage

GREEN TAG CERTIFIED





Copyright © Stormtech Pty Ltd. Patent 733361. Drawings not to scale, please use dimensions shown. Downloaded 04/05/2024 (please check for updates)