

ARCHITECTURAL

GRATES + DRAINS



65AR40 Linear Drain

The 65AR40 is our original premium architectural grate designed to be used with our Special Assembly units 65G100 and 65G90.

A 65mm wide UPVC channel is connected via downpipes at 200mm intervals to sockets in a 90mm or 100mm drain below. This allows the channel to be installed level while the drainpipe is given sufficient fall to be self-cleaning.


Please be aware that depending on the installation environment, for a pool installation or close to a surf beach, you may need to have your stainless steel grates electropolished.

This unique drainage system was recognised for its innovation by a DesignMark at the Australian International Design Awards.

SPECIFICATIONS + DIMENSIONS

Channel Width Channel Depth Length(s) Outlet Size 65mm 40mm 900mm 1000mm 1200mm 1500mm N/A

STORMTECH COLOUR FINISHES



Electroplate finishes subject to natural variation with time and local environment. Factors such as pools/surf beaches may require electropolishing. Contact us for suitability.


PRODUCT APPLICATIONS

Balcony Drainage Courtyard / Patio Drainage Pool and Spa Area Drainage Hospitality Drainage Paved Area Drainage Special Needs Drainage Threshold Drainage Suspended Slab Drainage

Copyright © Stormtech Pty Ltd. Patent 733361. Drawings not to scale, please use dimensions shown. Downloaded 09/05/2024 (please check for updates)

Visit **stormtech.com.au** for tools + inspiration.

Phone 1300 653 403 Email info@stormtech.com.au



Code 65AR40 Range Special Assembly Grate Style AR Category Components Channel Material Stainless Steel Steel Grade 316

Grates longer than 1500mm supplied in sections. Tile Inserts longer than 1200mm supplied in sections. Channels over 3000mm supplied in sections with joiner. +/-2mm tolerance on dimensions.