

ARCHITECTURAL

**GRATES + DRAINS** 



## 100Custom-316-A Linear Drain

316 stainless steel 100mm wide grate and custom channel depth.

Depth between 22mm and 100mm for a U shape channel. Depth between 40mm and 100mm for a recessed channel.

Available with a 3mm wire x 5mm gap, 5mm wire x 5mm gap, 5mm wire x 5mm gap Grate Grip slip resistant dimple finish and 2mm wire x 2.5mm gap grates

Suits Load Class A

For site specific needs or unusual situations, choose from our Custom Fabrication range.

Stormtech can customise any drainage requirements to achieve maximum efficiency.

## **SPECIFICATIONS + DIMENSIONS**

Channel Width Channel Depth Length(s) Outlet Size 110mm 22mm - 100mm As Required DN40, DN50, DN65, DN80, DN100

## STORMTECH COLOUR FINISHES




Electroplate finishes subject to natural variation with time and local environment. Factors such as pools/surf beaches may require electropolishing. Contact us for suitability.

## PRODUCT APPLICATIONS

Bathroom Drainage Aged / Health Care Drainage Balcony Drainage Commercial Drainage Courtyard / Patio Drainage Driveway Drainage Pool and Spa Area Drainage Hospitality Drainage Paved Area Drainage Shower Drainage Multi-Residential Drainage Special Needs Drainage

Copyright © Stormtech Pty Ltd. Patent 733361. Drawings not to scale, please use dimensions shown Downloaded 08/05/2024 (please check for updates)

Code 100Custom-316-A Range Custom Fabrication Grate Style CR Category Custom Made Channel Material Stainless Steel Steel Grade 316



Grates longer than 1500mm supplied in sections. Tile Inserts longer than 1200mm supplied in sections. Channels over 3000mm supplied in sections with joiner. +/-2mm tolerance on dimensions.



Visit **stormtech.com.au** for tools + inspiration.