



## 125Custom-316-B

#### **Linear Drain**

316 stainless steel 125mm wide grate and custom channel depth.

Depth between 27mm and 135mm.

Available with a 5mm wire x 5mm gap, 5mm wire x 5mm gap, 5mm wire x 5mm gap MORE GRIP slip resistant dimple finish

Suits Load Class B.

For site specific needs or unusual situations, choose from our Custom Fabrication range.

Stormtech can customise any drainage requirements to achieve maximum efficiency

### SPECIFICATIONS + DIMENSIONS

Channel Width 135mm
Channel Depth 27mm - 135mm
Length(s) As Required

**Outlet Size** DN40, DN50, DN65, DN80, DN100

### Powered Channel

Code 125Custom-316-B


**Category** Custom Made

Channel Material Stainless Steel

Grate Style CR

Steel Grade 316

Range Custom Fabrication



Grates longer than 1500mm supplied in sections. Tile Inserts longer than 1200mm supplied in sections. Channels over 3000mm supplied in sections with joiner. +/-2mm tolerance on dimensions.

#### SI ECII ICATIONS + DIMENSIONS

# STORMTECH COLOUR FINISHES





Electroplate finishes subject to natural variation with time and local environment. Factors such as pools/surf beaches may require electropolishing. Contact us for suitability.

#### PRODUCT APPLICATIONS

Bathroom Drainage Aged / Health Care Drainage Balcony Drainage Commercial Drainage Courtyard / Patio Drainage Driveway Drainage Pool and Spa Area Drainage Hospitality Drainage Paved Area Drainage Shower Drainage Multi-Residential Drainage Special Needs Drainage

GREEN TAO CERTIFIED





Copyright © Stormtech Pty Ltd. Patent 733361. Drawings not to scale, please use dimensions shown Downloaded 27/04/2025 (please check for updates)