

ARCHITECTURAL

GRATES + DRAINS

Code 65TiiCO25

Grate Style Ti

Steel Grade 316

Category Fixed-Length Units Channel Material Stainless Steel

72mm

Grates longer than 1500mm supplied in sections. Tile Inserts

longer than 1200mm supplied in sections. Channels over 3000mm supplied in sections with joiner. +/-2mm tolerance on

1.5mm

Range 65

11mm

dimensions

27mm



65TiiCO25 Tile Insert Drain

Full stainless steel drainage unit with centre outlet.

The 65Ti25 is a Tile Insert Drain manufactured from 1.5mm thick 316 marine grade stainless steel.

Suitable for tiles up to 10mm thick.

Refer to AS3500 for outlet pipe sizes specific to your installation.

SPECIFICATIONS + DIMENSIONS

Channel Width Channel Depth Length(s) Outlet Size 72mm 27mm 900mm 1000mm 1200mm DN50

STORMTECH COLOUR FINISHES



Electroplate finishes subject to natural variation with time and local environment. Factors such as pools/surf beaches may require electropolishing. Contact us for suitability.

PRODUCT APPLICATIONS

Bathroom Drainage Aged / Health Care Drainage Balcony Drainage Commercial Drainage Pool and Spa Area Drainage Hospitality Drainage Shower Drainage Multi-Residential Drainage Special Needs Drainage Threshold Drainage Suspended Slab Drainage Wet Area Drainage

Copyright © Stormtech Pty Ltd. Patent 733361. Drawings not to scale, please use dimensions shown. Downloaded 27/04/2025 (please check for updates)



Visit **stormtech.com.au** for tools + inspiration.

Phone 1300 653 403 Email info@stormtech.com.au