

ARCHITECTURAL

**GRATES + DRAINS** 



## 250Custom-304-C Linear Drain

304 stainless steel 250mm wide grate and custom channel depth.

Depth between 42mm and 260mm.

Available with a 5mm wire x 5mm gap and 5mm wire x 5mm gap Grate Grip slip resistant dimple finish

Suits Load Class C.

For site specific needs or unusual situations, choose from our Custom Fabrication range.

Stormtech can customise any drainage requirements to achieve maximum efficiency

## **SPECIFICATIONS + DIMENSIONS**

Channel Width Channel Depth Length(s) Outlet Size 260mm 42mm - 260mm As Required DN40, DN50, DN65, DN80, DN100

## STORMTECH COLOUR FINISHES



Electroplate finishes subject to natural variation with time and local environment. Factors such as pools/surf beaches may require electropolishing. Contact us for suitability.

## **PRODUCT APPLICATIONS**

Bathroom Drainage Aged / Health Care Drainage Balcony Drainage Commercial Drainage Courtyard / Patio Drainage Driveway Drainage Pool and Spa Area Drainage Hospitality Drainage Paved Area Drainage Shower Drainage Multi-Residential Drainage Special Needs Drainage

Copyright © Stormtech Pty Ltd. Patent 733361. Drawings not to scale, please use dimensions shown. Downloaded 27/04/2025 (please check for updates)



Visit **stormtech.com.au** for tools + inspiration.

Phone 1300 653 403 Email info@stormtech.com.au



Code 250Custom-304-C Range Custom Fabrication Grate Style CR Category Custom Made Channel Material Stainless Steel Steel Grade 304

	– 258mm –		1	
<u>a a a a a a</u>		0000		
			HL.	40mm Minimum
				250mm Maximum

Grates longer than 1500mm supplied in sections. Tile Inserts longer than 1200mm supplied in sections. Channels over 3000mm supplied in sections with joiner. +/-2mm tolerance on dimensions.