




65TR40

Linear Drain



65mm wide UPVC channel is connected via downpipes at 200mm intervals to sockets in a 100mm drain below. This allows the channel to be installed level while the drainpipe is given sufficient fall to be self-cleaning.

Please note that our TR grates have a non linished finish.

Please be aware that depending on the installation environment, for a pool installation or close to a surf beach, you may need to have your stainless steel grates electropolished.

This unique drainage system was recognised for its innovation by a DesignMark at the Australian International Design Awards.



SPECIFICATIONS + DIMENSIONS

Channel Width 65mm Channel Depth 40mm

Length(s) 900mm 1000mm 1200mm 1500mm

Outlet Size N/A



Code 65TR40
Range Special Assembly
Grate Style TR
Category Components
Channel Material Stainless Steel
Steel Grade 316

Grates longer than 1500mm supplied in sections. Tile Inserts longer than 1200mm supplied in sections. Channels over 3000mm supplied in sections with joiner. +/-2mm tolerance on dimensions.

STORMTECH COLOUR FINISHES





Electroplate finishes subject to natural variation with time and local environment. Factors such as pools/surf beaches may require electropolishing. Contact us for suitability.

PRODUCT APPLICATIONS

Balcony Drainage Courtyard / Patio Drainage Pool and Spa Area Drainage Hospitality Drainage Paved Area Drainage Special Needs Drainage Threshold Drainage Suspended Slab Drainage







Copyright © Stormtech Pty Ltd. Patent 733361. Drawings not to scale, please use dimensions shown. Downloaded 06/12/2025 (please check for updates)