

ARCHITECTURAL

GRATES + DRAINS

Code 38PS40

Grate Style PS

Steel Grade 316

dimensions.

Range Special Assembly

Category Components

Channel Material Stainless Steel

Grates longer than 1500mm supplied in sections. Tile Inserts longer than 1200mm supplied in sections. Channels over

3000mm supplied in sections with joiner. +/-2mm tolerance on



38PS40 Linear Drain

This is our Punched Slot grate for use with the 38G90 and 38G100 Special Assembly drain.

A 38mm wide UPVC channel is connected via downpipes at 200mm intervals to sockets in a 90mm or 100mm drain below. This allows the channel to be installed level while the drainpipe is given sufficient fall to be self-cleaning.

Please be aware that depending on the installation environment, for a pool installation or close to a surf beach, you may need to have your stainless steel grates electropolished.

This unique drainage system was recognised for its innovation by a DesignMark at the Australian International Design Awards.

SPECIFICATIONS + DIMENSIONS

Channel Depth **Outlet Size**

900mm 1000mm 1200mm 1500mm

STORMTECH COLOUR FINISHES



Electroplate finishes subject to natural variation with time and local environment. Factors such as pools/surf beaches may require electropolishing. Contact us for suitability.

PRODUCT APPLICATIONS

Bathroom Drainage Balcony Drainage Commercial Drainage Courtyard / Patio Drainage Pool and Spa Area Drainage Paved Area Drainage

Phone 1300 653 403

Shower Drainage Special Needs Drainage Threshold Drainage Suspended Slab Drainage Wet Area Drainage

Copyright © Stormtech Pty Ltd. Patent 733361. Drawings not to scale, please use dimensions shown. Downloaded 04/09/2025 (please check for updates)



Visit **stormtech.com.au** for tools + inspiration.

Email info@stormtech.com.au

Length(s)

Channel Width

38mm 40mm N/A