

ARCHITECTURAL

GRATES + DRAINS



125Custom-316-A Linear Drain

316 stainless steel 125mm wide grate and custom channel depth.

Depth between 22mm and 135mm.

Available with a 3mm wire x 5mm gap, 5mm wire x 5mm gap, 5mm wire x 5mm gap MORE GRIP slip resistant dimple finish

Suits Load Class A

For site specific needs or unusual situations, choose from our Custom Fabrication range.

Stormtech can customise any drainage requirements to achieve maximum efficiency

SPECIFICATIONS + DIMENSIONS

Channel Width Channel Depth Length(s) Outlet Size 135mm 22mm - 135mm As Required DN40, DN50, DN65, DN80, DN100

STORMTECH COLOUR FINISHES



Electroplate finishes subject to natural variation with time and local environment. Factors such as pools/surf beaches may require electropolishing. Contact us for suitability.

PRODUCT APPLICATIONS

Bathroom Drainage Aged / Health Care Drainage Balcony Drainage Commercial Drainage Courtyard / Patio Drainage Driveway Drainage Pool and Spa Area Drainage Hospitality Drainage Paved Area Drainage Shower Drainage Multi-Residential Drainage Special Needs Drainage

Copyright © Stormtech Pty Ltd. Patent 733361. Drawings not to scale, please use dimensions shown. Downloaded 15/09/2025 (please check for updates)




Visit **stormtech.com.au** for tools + inspiration.

Phone 1300 653 403 Email info@stormtech.com.au



Code 125Custom-316-A Range Custom Fabrication Grate Style CR Category Custom Made Channel Material Stainless Steel Steel Grade 316



Grates longer than 1500mm supplied in sections. Tile Inserts longer than 1200mm supplied in sections. Channels over 3000mm supplied in sections with joiner. +/-2mm tolerance on dimensions.